



POSSAFE
SOLIDLY RELIABLE

Possafe LBS 300 Kablolu Okuyucu



1D/ 2D
Okuma



EI Tipi



USB



Yüksek
Performans



CE  **RoHS** **FC**
2002/95/EC

TEKNİK ÖZELLİKLER

Işık Kaynağı	617 nm LED Odaklama, Beyaz LED		
Desteklenen Barkod Türleri	1D: Code 128, EAN-13, ISBN, ISSN, Code 32, EAN-8, UPC-A, UPC-E, UCC/EAN-128, Code 39, Codabar, Code 93, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, IATA 2 of 5, Matrix 2 of 5, Code 11, MSI-Plessey, UK, GSI DataBar, GSI DataBar Limit, GSI DataBar Expand, Datalogic 2 of 5. 2D: QR Code, Data Matrix, PDF417, Aztec, Hanxin.		
Çözünürlük	640(H) × 480(V) Pixel CMOS		
Mesafe	EAN13: 25 ~ 150 mm (13 mil) QR: 10 ~ 120 mm (15 mil) PDF147: 30 ~ 110 mm (13 mil)		
Tarama Modu	Manuel, Sürekli, Otomatik	Tarama Hızı	500 / sn
Görüş Açısı	Döndürme 360° / Eğim ±55° / Aralık ±55°		
Min. Tanıma	≥ 5 mil	Baskı Kontrastı	%20
Bit Hata Oranı	1/5 milyondan az	Arayüz	USB-HID, USB-COM, RS232
Materyal	ABS + PC	Kablo	2 m – Düz
Gerilim	DC 5V ± %5	Çalışma Akımı	170 mA
Çalışma Ortamı	Sıcaklık -20°C ~ 50°C	Nem %5~95 (yoğuşmasız)	
Depolama Ortamı	Sıcaklık -40°C ~ 70°C		
Ortam Işığı	0~100000 Lux		
Düşme Şok Direnci	3 metreden betona birden fazla düşmeye karşı dayanıklıdır.		
Boyutlar / Ağırlık	176 × 100 × 72 mm	177 gr	



* Yukarıdaki parametreler önceden bildirilmeksizin değiştirilebilir.